



KÖSTER Caulking Gun

Technical Data Sheet J 989

Issued: 2022-07-01

For standard 310 ml cartridges and tubular bag up to 400 ml content

Features

The KÖSTER Caulking Gun is a robust and reliable hand injection pump for installing 310 ml KÖSTER KB-Flex 200 and KÖSTER Crisin Cream cartridges, as well as tubular bags up to 410 ml content. A push plate for pressing tubular bags is included in the scope of delivery.

Technical Data

Mechanical thrust ratio	14:1
Distance per Stroke	6 mm
Maximum force	2.5 kN
Carriage Length	239 mm (9.42 in)
Inside diameter	50 mm
Cartridge capacity	310ml (10.5oz)
Ø Push plate for cartridges	approx. 39 mm (metal)
Ø Push plate for tubular bags	approx. 50 mm (plastic)
Weight	approx. 1 kg

Fields of Application

Closed hand press, suitable for high and low viscosity materials. The special push rod made of galvanized steel ensures an even and stable conveyance.

The KÖSTER Caulking Gun is delivered with a pre-assembled plastic push plate for tubular bags. To process cartridges, the plastic push plate must be removed and the steel push plate for cartridges installed.

For further information on processing, please read the information in the technical data sheets for KÖSTER KB-Flex 200 and KÖSTER Crisin Creme.

Cleaning

After use clean the KÖSTER Special Caulking Gun, tools and any residues with a cloth or paper towels, oily residue can be removed with KÖSTER Universal Cleaner.

Packaging

J 989 001

piece

Storage

When stored clean and dry there is no limited storage time.

Safety

Observe all Local, State, and Governmental saftety requirements when using tools of all types.

Related products

KÖSTER Cleaning Brush	Prod. code IN 959 001
KÖSTER KB-Flex 200	Prod. code J 250
KÖSTER Crisin Cream	Prod. code M 278
KÖSTER Spatula	Prod. code X 987 001

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The proper and thereby effective and successful application of our products is not subject to our control. The installer is responsible for the correct application under consideration of the specific conditions of the construction site and for the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which exceed the specifications contained in this technical guideline require written confirmation. The valid standards for testing and installation, technical guidelines, and acknowledged rules of technology have to be adhered to at all times. The warranty can and is therefore only applied to the quality of our products within the scope of our terms and conditions, not however, for their effective and successful application. This guideline has been technically revised; all previous versions are invalid.

KÖSTER BAUCHEMIE AG • Dieselstraße 1-10 • D-26607 Aurich • Tel. 04941/9709-0 • Fax -40 • info@koester.eu • www.koester.eu